

2003 H2

Off-road capabilities and toughness of a HUMMER. Interior refinements you've never seen from HUMMER before. Built in an all-new state-of-the-art facility, it's a totally new addition to the HUMMER family. And a totally new addition to the SUV category. Extremely capable. Competitively priced. The new H2. In dealerships summer 2002.





COMPONENTS & FEATURES

- Engine: Vortec 6000 6.0L V8 with cast iron block, cast aluminum cylinder heads and sequential fuel injection
Horsepower (SAE hp): (est.) 320 @ 5000 rpm
Torque (lb.-ft./Nm): (est.) 360 @ 4000 rpm
- Transmission: 4L65-E 4-speed automatic
- Drivetrain: Borg-Warner 2-speed electronically controlled full-time 4WD
- Traction Control System (TCS): Brake controlled, single-wheel control capability with rear axle locking differential
- Fuel capacity: 32 gallon tank
- Steering: Variable ratio, power assisted
- Brakes: 4-wheel disc, 4-wheel/4-channel ABS and dual piston calipers with Dynamic Rear Proportioning
- Front suspension: Independent with torsion bars, 46mm monotube gas shocks and 35.9mm front stabilizer bar
- Rear suspension: 5-link variable-rate coil spring, solid axle and 30mm stabilizer bar
- Frame: 3-piece fully welded ladder-type

SPECIFICATIONS & PERFORMANCE DATA

- Length: 189.8 in.
- Height: 77.8 in.
- Width (excluding mirrors): 81.2 in.
- Track width: 69.4 in.
- Wheelbase: 122.8 in.
- Ground clearance: 9 in.
- Approach angle: 43.6° (with optional LT315/70R-17 off-road tires)
- Departure angle: 39.7° (with optional LT315/70R-17 off-road tires)
- Maximum towed load: 7,000 lb. (NOTE 1)
- Water fording depth: 20 in.

WHEELS & TIRES

- 17 in. cast aluminum wheels
- All-terrain LT285/70R-17 tires with full-sized spare

EXTERIOR FEATURES

- Retrieval loops and access hole for hitch/winch receiver on front bumper
- Tow loops and access hole for class 3 hitch on rear bumper
- Full underbody/rocker panel protection
- Power-folding, heated outside rearview mirrors with curb assist feature

INTERIOR FEATURES

- Front air bags (NOTE 2)
- Driver's seat with standard memory feature for 2 drivers
- Tan wheat cloth seats with 8-way power adjustment for front passengers
- Available seating for 6
- Multi-function driver information center
- 6 power points (cigarette lighter, 2 front, 2 rear and 1 tailgate accessible)
- Dual zone heating, ventilation and A/C units with rear controls
- RDS radio with CD, THEFTLOCK® security and 9-speaker Bose® sound system
- Rear seat audio controls with headphone jacks
- 60/40 split second row seats
- Triple sealed doors and enhanced acoustical insulation
- Electrochromic inside rearview mirror with compass and outside temperature display
- OnStar® system
- Content alarm anti-theft system
- PASSLock® anti-theft vehicle security system
- Panic button with remote keyless entry
- Leather wrapped steering wheel with secondary audio controls
- Rear compartment cargo and tailgate tie-downs

OPTIONAL EQUIPMENT

- Self-leveling rear air suspension with on-board air compressor
- LT315/70R-17 off-road tires with full-sized spare
- Heated leather seats
- Third row seating
- 6-disc CD changer
- Moonroof
- Roof mounted luggage basket
- Hard roof-mounted cargo carrier
- Double crossbar roof rack in Black or Brushed Aluminum
- Brush guard (flat or wraparound)
- Chrome accents
- Tubular assist steps or removable U steps
- Tubular tail lamp covers
- Off-road lights

HUMMER® like nothing else.™



Black



White



Yellow



Sunset Orange
Metallic



Red
Metallic



Pewter
Metallic



Sage Green
Metallic

For more information check out www.HUMMER.com or call us at 1.800.REAL.4WD.

©General Motors Corporation, 2002. HUMMER and the vehicle's grille design are registered trademarks of General Motors Corporation. **NOTE 1:** Trailer tongue weight should be 10–15% of trailer, 1,000 lbs. maximum. Do not exceed the maximum allowable tongue weight for your vehicle Gross Combination Weight Rating (GCWR), which is the total allowable weight of the completely loaded vehicle and trailer including any passengers, cargo, equipment and conversions, is 14,000 lbs. If you'll be pulling a trailer that, when loaded, will weigh more than 4,000 lbs., be sure to use a properly mounted, weight distributing hitch and sway control of the proper size. If your trailer weighs more than 2,000 lbs. loaded, then it needs its own brakes, and they must be adequate. **NOTE 2:** Always use safety belts and proper child restraints, even with air bags. Children are safer when properly secured in a rear seat. Pictured vehicles may vary from actual production models. Manufacturer reserves the right to change prices, colors, materials, equipment and specifications at any time and without prior notice. Details and specifications may vary according to local regulations and conditions.